

# MYSTICAL

CERAMIC WALL TILES



eliane

## MYSTICAL CERAMIC WALL TILES

### Perseu Perola



30x90 cm | 12"x36"  
MT ( Metallic )

### Perseu Dark



30x90 cm | 12"x36"  
MT ( Metallic )

### Tetris Perola



30x90 cm | 12"x36"  
MT ( Metallic )

### Tetris Ouro



30x90 cm | 12"x36"  
MT ( Metallic )



WALLS



FIRE PROOF



VOC FREE

# MYSTICAL

## CERAMIC WALL TILES

### SIZES AND PACKING

Type / Size	Finish	Rectified	Unit	Work Size	Thick	Faces	Sqft/ Carton	Pieces/ Carton
Wall Tiles 12"x36"	MT (Metallic)	Yes	PC	300 x 900 mm 12" x 35 1/2"	9.3 mm	1	5.81	2

### USAGE RECOMMENDATION

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	
Wet & Level - Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (Including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes - Interior (Residential or Commercial)	N/A	✓*
Countertops	N/A	
Facades	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3.

\* Check Specialty Product Disclaimer and Special Cleaning Instructions on Installation and Care.

### INSTALLATION AND CARE

Grout Joint Recommendation: 1/16"

Shade Variation: V1

Professional tile installation is recommended. For complete installation instructions consult the TCNA Handbook for Ceramic, Glass, and Stone Tile Installation. Follow the grout manufacturer instructions for the complete removal of grout and construction residue from initial installation.

#### \*SPECIALTY PRODUCT DISCLAIMER:

*This is a finely decorative Specialty Product with metallic or distinctive glazing finishes. THESE TILES ARE SUBJECT TO SURFACE DAMAGE WHEN EXPOSED TO PHYSICAL OR CHEMICAL FORCES.*

**SPECIAL CLEANING INSTRUCTIONS:** *These tiles have a special decorative finish with precious metals or distinctive glazing, therefore should be cleaned only with a cloth soaked in water and neutral detergent. Do not use acidic cleaning products or abrasive sponges that may damage the tiles' surface.*

### QUALITY

#### WARRANTY

Standard quality tiles manufactured by Eliane Ceramic Tiles meet or exceed ISO 13006 and ANSI A137.1 standards.

#### VOC FREE

Eliane ceramic and porcelain tiles are low-emitting materials with zero emission of volatile organic compounds (VOC).

#### FIRE PROOF

Our ceramic and porcelain tiles are NOT flammable, except mesh material of mesh mounted mosaics.

### PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	≤ 20%
Breaking Strength	C648	≥ 125 lbs
DCOF WET	ANSI A137.1 ANSI A326.3	N/A
Scratch Hardness	MOHS	4
Frost Resistance	C1026	No
Chemical Resistance	C650	Class E
Stain Resistance	C1378	Class A





