

EDEN™

GLAZED PORCELAIN STONEWARE



EDEN™

GLAZED PORCELAIN STONEWARE



Bianco 3x11



Cotone 3x11



Greige 3x11



Fango 3x11



Ottanio 3x11




Bianco Hexagon



Cotone Hexagon



Greige Hexagon



Fango Hexagon



Ottanio Hexagon



Bianco DecoroTapetto 2



Cotone DecoroTapetto 2

SIZES		SQ. FT./ CARTON	PIECES/ CARTON	CARTONS/ PALLET	SQ. FT./ PALLET	LBS/ CARTON
3 x 11 Floor Tile	(2-3/4" x 11")	10.5	50	52	546.00	43.05
7x8 Hexagon Floor Tile	(7.16" x 8.26")	4.9388	16	100	493.88	21.77
7x8 Decoro Tapetto 2	(7.16" x 8.26")	4.9388	16	100	493.88	21.77

GROUT JOINT
RECOMMENDATION

1/8"

SHADE VARIATION

V2

Medium
(V2)

V3

High (V3)
Cotone Only

APPLICATIONS

Dry & Level – Interior Floor

Wet & Level – Interior Floor

Shower Floors (Residential or Light Commercial)

Exterior Floor Applications
(including pool decking & other wet areas with minimal
footwear)

Ramps & Inclines

Walls/Backsplashes

Countertops

Pool Linings

TARGET
DCOF WET

N/A

≥ 0.42

≥ 0.42

≥ 0.60

≥ 0.65

N/A

N/A

N/A

SUITABLE

•

•

•

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6.

PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	7.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

USAGE

FLOORS	WALLS	COUNTERTOPS
F	W	C

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.



Floor Tile



Wall Tile



Reveal Imaging®



Pre-Consumer
Recycled Content



3215 Corridor Dr. Mira Loma, Ca Ph. 626.961.0051 Fax. 626.336.2217